



Safie RE D190 MI 2100 DALI 840 White C4L-3m

Article number 60628402120

Product feature

Driver type	DALI-2
Material of housing	Aluminium
Diffuser/optics	Reflector
Color of reflector	Mirror
Light source	Integrated LED
Color of housing	White
RAL	9016
Gtin	7333160037757

Installation data

Mounting	Recessed; Surface
Cable entries	1
Connection	3 m 4-lead cable
Cut out (mm)	160

Lifetime

Calculated LED lifetime, L70 (h)	100 000
Calculated LED lifetime, L80 (h)	100 000

Photometric data

Color T (K)	4000
Color Rendering Index (CRI)	≥80
Beam angle (°)	60
Beam description	Medium
Unified Glare Rating (UGR)	≤19
Efficacy (lm/W)	147
Flux (lm)	2200
SDCM	≤3

Technical data

IP class	IP20; IP54
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+40
Compliance	ErP; CE; REACH; RoHS
Guarantee (years)	5

Measurements

Height/depth (mm)	61
Diameter (mm)	190
Net weight (kg)	0.5

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 2
Power (W)	15
Standby power (W)	0.5
Type Of Connection	Push-in terminal
Qty per B16 MCB	112
Qty per C10 MCB	70
Qty per C16 MCB	112
Power factor	≥0.90

