

57010020

Modular fuse holder for cylindrical fuses RM FUSE SWITCH 32A 2P



Strong points

- Improved safety
- High breaking capacity
- Format and specific accessories

Compliance with standards

- IEC 60269-2-1
- IEC 60269-1
- IEC 60269-2
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620
- CSA 265615
- UL E307648

Link to the reference



<https://emea.socomec.com/en/reference/57010020>

RM are modular fuse disconnect switches for cylindrical fuses. They provide safety disconnection and protection against overloads and short-circuits in any low voltage electrical circuit.

RM: Non-signalling fuse disconnect switches for fuses without strikers.

Classification

UNSPSC	39121624
ETIM Class	EC002705
IGCC	4974

Commerce

Effective date	2012-06-25
Offer Life Cycle Code	40
Country of origin	ES

ETIM - Electrical characteristics

Nominal voltage [V]	690
Number of poles	2
Concurrently switching neutral conductor	No

ETIM - Mechanical characteristics

Mounting method	DIN rail
For fuse size	10x38 mm
Width in number of modular spacings	2
Built-in depth [mm]	40
Degree of protection (IP)	IP2X

ETIM - Technical features

Lockable	Yes
With optical defect indication	No

Logistics

GTIN/EAN	3596032686932
Customs number	8536105090
Price unit	PC
Weight of the packing unit [kg]	0.12
Length of the packing unit [m]	0.065
Width of the packing unit [m]	0.035
Depth of the packing unit [m]	0.09

Norms

Conformity to standards	IEC UL
-------------------------	------------

Technical Characteristics

Height [mm]	78
Width [mm]	70
Depth [mm]	58
Weight [kg]	0.12
Fuse melting indicator	No
Fuse size	10x38
Number of poles	2
Rated current [A]	32
Size	RM32