
Brahe Panel RE 595x595 2xLinear LS 2600 DALI 830 White C4L-3m

Article number 32208302620

Brahe Panel is a LED-panel equipped with two 300x60 mm downlights with the latest LED technology for maximum efficiency and optimal light distribution. Its high-quality lens and reflector technology minimize glare and provide precise and pleasant lighting.



Product feature

Driver type	DALI-2
Material of housing	ASA
Diffuser/optics	Lens (L)
Light source	Integrated LED
Color of housing	White
RAL	9016
Gtin	7333160042188

Installation data

Mounting	Recessed
Installation (surface)	Ceiling
Connection	Cable
Length cable (m)	3
Material cable	Halogen free

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 2
Power (W)	18
Standby power (W)	0.5
Qty per B16 MCB	112
Qty per C10 MCB	70
Qty per C16 MCB	112

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam angle (°)	65
Beam description	Medium
Unified Glare Rating (UGR)	≤19
Efficacy (lm/W)	141
Flux (lm)	2530
SDCM	≤3

Technical data

IP class	IP20
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+30
Calculated LED lifetime, L70 (h)	>100 000
Calculated LED lifetime, L80 (h)	>100 000
Calculated LED lifetime, L90 (h)	100 000
Driver lifetime (h)	100 000
Compliance	CE; REACH

Measurements

Length (mm)	595
Height/depth (mm)	43
Width (mm)	595
Net weight (kg)	2.654

