

**Sevede RE L625 OP 23W 2500
ActiveAhead-2 without sensor 830
White**

Article number 36548302557



Product feature

Wireless controls	ActiveAhead
Technology	BT Mesh
Material of housing	Aluminium (Recycled)
Diffuser/optics	Opal
Color of reflector	White
Light source	Integrated LED
Color of housing	White
RAL	9016

Installation data

Mounting	Recessed
Connection	Cable
Length cable (m)	2.5
Material cable	Halogen free

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	23
Standby power (W)	0.5
Qty per B16 MCB	36
Qty per C10 MCB	37
Qty per C16 MCB	60
Power factor	≥0.95

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam angle (°)	110
Beam description	Wide
Efficacy (lm/W)	106
Flux (lm)	2440
SDCM	≤3

Technical data

IP class	IP20
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+35
Calculated LED lifetime, L80 (h)	100 000
Driver lifetime (h)	100 000
Compliance	CE; REACH; ENEC
Guarantee (years)	5

Measurements

Length (mm)	620
Height/depth (mm)	60
Width (mm)	75
Net weight (kg)	1.4

