

HRC cartridge fuses



Technical data and dimensions (p. 102-103)

Pack	Cat.Nos		Cylindrical type gG			Pack	Cat.Nos		Cylindrical type aM (motor rated)		
			Conform to NF C 63-210/211 - EN 60269-1 and 2 and IEC 60269-1, 2 and 2-1 Veritas approved						Conform to NF C 60-200 - EN 60269-1 IEC 60269-1 Veritas approved		
	Without indicator	With indicator	Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps)		Without indicator	With indicator	Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps)
			10 x 38 HRC						8.5 x 31.5		
10	133 94		0.5			10	120 01		1		
10	133 01		1			10	120 02		2		
10	133 02	134 02	2			10	120 04		4	400	20 000
10	133 04	134 04	4			10	120 06		6		
10	133 06	134 06	6			10	120 08		8		
10	133 08	134 08	8	500	100 000	10	120 10		10		
10	133 10	134 10	10						Conform to NF C 63-210/211 - EN 60296-1 IEC 60269-1, 2 and 2-1 Veritas approved		
10	133 12	134 12	12						10 x 38 HRC		
10	133 16	134 16	16						0.25		
10	133 20	134 20	20						0.50		
10	133 25	134 25	25						1		
			14 x 51 HRC			10	130 92		2		
10	143 02		2			10	130 95		4		
10	143 04		4			10	130 01		6	500	100 000
10	143 06	145 06	6			10	130 02		8		
10	143 10	145 10	10			10	130 04		10		
10	143 16	145 16	16	500	100 000	10	130 06		12		
10	143 20	145 20	20			10	130 08		16		
10	143 25	145 25	25			10	130 10		20	400	
10	143 32	145 32	32			10	130 12		25	400	
10	143 40	145 40	40			10	130 16		14 x 51 HRC		
10	143 50 ⁽¹⁾	145 50 ⁽¹⁾	50			10	130 20 ⁽²⁾		2		
			22 x 58 HRC			10	130 25 ⁽²⁾		4		
10	153 04		4			10	140 02	141 02	6		
10	153 06		6			10	140 04	141 04	8		
10	153 10		10			10	140 06	141 06	10		
10	153 16		16			10	140 08	141 08	12	500	100 000
10	153 20		20			10	140 10	141 10	16		
10	153 25	155 25	25	500	100 000	10	140 12	141 12	20		
10	153 32	155 32	32			10	140 16	141 16	25		
10	153 40	155 40	40			10	140 20	141 20	32		
10	153 50	155 50	50			10	140 25	141 25	40		
10	153 63	155 63	63			10	140 32	141 32	45	400	
10	153 80	155 80	80			10	140 40	141 40	50	400	
10	153 96	155 96	100			10	140 45 ⁽¹⁾	141 45 ⁽¹⁾	22 x 58 HRC		
10	153 97 ⁽¹⁾	155 97 ⁽¹⁾	125	400		10	140 50 ⁽¹⁾	141 50 ⁽¹⁾	25		
						10	150 25	151 25	32		
						10	150 32	151 32	40	500	100 000
						10	150 40	151 40	50		
						10	150 50	151 50	63		
						10	150 63	151 63	80		
						10	150 80	151 80	100		
						10	150 96	151 95	125	400	
						10	150 97	151 97			



Isolating fuse carriers 8.5 x 31.5 and 10 x 38

see p. 133

Neutral links

10	123 00	8.5 x 31.5
10	133 00	10 x 38
10	143 00	14 x 51
10	153 00	22 x 58



(1) Overrating described by standards
(2) Overrating not described by standards