

Z44 CE L1200 29W 4500 DALI 830

Article number 51388304820



Product feature		Photometric data	
Driver type	DALI-2	Color T (K)	3000
Material of housing	Aluzink coated sheet steel	Color Rendering Index (CRI)	≥80
Material of diffuser/optics	Acrylic (PMMA)	Light distribution	Direct
Diffuser/optics	Linear prismatic	Beam description	Wide
Light source	Integrated LED; Replaceable LED	Unified Glare Rating (UGR)	≤25
Color of housing	White	Efficacy (lm/W)	150
Installation data		Flux (lm)	4340
Mounting	Surface	SDCM	≤3
Installation (surface)	Wall	Technical data	
Cable entries	2+2	IP class	IP44
Connection	Terminal block 5x2.5	IK class	IK03
Looping	Available upon request	Ambient temp, min (°C)	-25
Through wiring	Available upon request	Ambient temp, max (°C)	+30
Lifetime		Compliance	CE; REACH
Calculated LED lifetime, L80 (h)	>100 000		
Calculated LED lifetime, L90 (h)	55,000		
Driver lifetime (h)	100,000		

Measurements

Length (mm)	1192
Height/depth (mm)	60
Width (mm)	176
Net weight (kg)	2.3

Electrical data

Frequency (Hz)	50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	29
Standby power (W)	0.5
Available with	Integrated sensor; DALI
Qty per B16 MCB	55
Qty per C10 MCB	57
Qty per C16 MCB	93
Power factor	≥ 0.90

