

Kleva CE L600 15W 2200 DALI 830

Article number 51328302220



Product feature	
Driver type	DALI-2
Material of housing	Aluminium (Recycled)
Material of diffuser/optics	Polycarbonate (PC)
Diffuser/optics	Linear prismatic; Opal
Light source	Integrated LED
Color of housing	White
RAL	9003
Gtin	7333160041297

Photometric data	
Color T (K)	3000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam description	Very wide
Efficacy (lm/W)	144
Flux (lm)	2160
SDCM	≤3

Installation data	
Mounting	Surface
Cable entries	4
Connection	Terminal block 5x2.5
Looping	Yes
Through wiring	Available upon request

Lifetime	
Calculated LED lifetime, L80 (h)	>100 000
Calculated LED lifetime, L90 (h)	100 000
Driver lifetime (h)	100 000

Technical data	
IP class	IP44
IK class	IK07
Ambient temp, min (°C)	-25
Ambient temp, max (°C)	+40
Compliance	CE; REACH; ENEC
Guarantee (years)	5

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	15
Standby power (W)	0.3
Qty per B16 MCB	55
Qty per C10 MCB	57
Qty per C16 MCB	93
Power factor	≥ 0.90

Measurements

Length (mm)	625
Height/depth (mm)	66
Width (mm)	110
Net weight (kg)	1.3

