



## "waterproof" for encapsulation




**WP 0606 B**

- 1.5-6 mm<sup>2</sup>, Cu 3~

PC



RAL  
9011




- with terminals
- 5-pole per pole 6 x 1,5 mm<sup>2</sup> sol / f, 4 x 2,5 mm<sup>2</sup> sol / f, 4 x 4 mm<sup>2</sup> sol / f, 4 x 6 mm<sup>2</sup> sol / f, 2 x 10 mm<sup>2</sup> sol / f
- Cable entries via knockouts, order ASS separately (see cable entry systems LES)
- cable junction box for encapsulating
- for ground installation without live loads or in risk of condensation formation and ingress of liquids
- installation under water without chemical additives up to a depth of 1 meter possible in the long term
- usable for heating cable / heating tape up to max. 70 °C surface temperature
- with sealing compound and sealing plug
- in case of re-installation or testing the sealing compound can be removed easily
- durability of sealing compound to processing ≥ 12 months
- enclosure volume 850 ml
- colour: black, RAL 9011

Degree of protection:	For totally encapsulated cable junction boxes the degree of protection of enclosures according to DIN EN 60529 is not applicable.
rated insulation voltage	Ui = 690 V a.c./d.c.
current carrying capacity	40 A
tightening torque for terminal	1,5 Nm
Material:	PC-GFS (polycarbonate)
width	130 mm
height:	130 mm
depth	77 mm
Weight	1,344 kg
in accordance with	DIN VDE V 0606-22-100

## Drawings

Dimension drawing



”waterproof“ for encapsulation



**WP 0606 B**

- 1.5-6 mm<sup>2</sup>, Cu 3~


PC



RAL  
9011



Detail mass



Operating and ambient conditions

Application area	Suitable for outdoor installation (harsh environment and/or outdoor). For application in ambient conditions with formation of condensation and ingress of water as well as for installation in the ground without traffic loads in accordance with DIN VDE V 0606-22-100
Resistant to occasional cleaning procedures (direct jet)	Resistant to occasional cleaning procedures (direct jet) with high-pressure cleaner without additives, water temperature: max. 80° C
Ambient temperature	Average value over 24 hours + 55 °C Maximum value + 70 °C Minimum value - 25 °C
Relative humidity	100 %
Burning behaviour	Glow wire test IEC 60 695-2-11: 960 °C UL Subject 94: V-0 flame-retardant self-extinguishing
Degree of protection against mechanical load	IK09 (10 Joule)