

**57025014**

## Modular fuse holder for cylindrical fuses RMS FUSE SWITCH 50A 3+N

RMS are modular fuse disconnect switches for cylindrical fuses. They provide safety disconnection and protection against overloads and short-circuits in any low voltage electrical circuit.

RMS: Fuse disconnect switches with pre-break auxiliary contact that signals that the fuse is present / blown.

### Strong points

- Improved safety
- High breaking capacity
- Format and specific accessories

### Compliance with standards

- IEC 60269-2-1
- IEC 60269-1
- IEC 60269-2
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620
- CSA 265615
- UL E307648

### Link to the reference



<https://emea.socomec.com/en/reference/57025014>

### Classification

UNSPSC	39121624
ETIM Class	EC002705
IGCC	4974

### Commerce

Effective date	2005-11-23
Offer Life Cycle Code	40
Country of origin	ES

### ETIM - Electrical characteristics

Nominal voltage [V]	690
Number of poles	4
Concurrently switching neutral conductor	Yes

### ETIM - Mechanical characteristics

Mounting method	DIN rail
For fuse size	14x51 mm
Width in number of modular spacings	4
Built-in depth [mm]	49.5
Degree of protection (IP)	IP2X

### ETIM - Technical features

Lockable	Yes
With optical defect indication	Yes

### Logistics

GTIN/EAN	3596031808151
Customs number	8536105090
Price unit	PC
Weight of the packing unit [kg]	0.48
Length of the packing unit [m]	0.09
Width of the packing unit [m]	0.12
Depth of the packing unit [m]	0.13

### Norms

Conformity to standards	IEC UL
-------------------------	-----------

### Technical Characteristics

Height [mm]	110
Width [mm]	106
Depth [mm]	76
Weight [kg]	0.48
Fuse melting indicator	Yes
Fuse size	14x51
Number of poles	3+N

Rated current [A]	50
Size	RM/RMS 50