

**Sevede WA L1200 Asym 18W 2200  
ActiveAhead-2 830 White**

Article number 26908302256



**Product feature**

|                            |                      |
|----------------------------|----------------------|
| <b>Wireless controls</b>   | ActiveAhead          |
| <b>Technology</b>          | BT Mesh              |
| <b>Driver type</b>         | Freedom              |
| <b>Sensor type</b>         | PIR                  |
| <b>Material of housing</b> | Aluminium (Recycled) |
| <b>Diffuser/optics</b>     | Opal                 |
| <b>Color of reflector</b>  | White                |
| <b>Light source</b>        | Integrated LED       |
| <b>Color of housing</b>    | White                |
| <b>RAL</b>                 | 9016                 |
| <b>Gtin</b>                | 7333160038433        |

**Electrical data**

|                          |         |
|--------------------------|---------|
| <b>Frequency (Hz)</b>    | 0/50-60 |
| <b>Voltage (V)</b>       | 220-240 |
| <b>Isolation</b>         | Class 1 |
| <b>Power (W)</b>         | 18      |
| <b>Standby power (W)</b> | 0.5     |
| <b>Qty per B16 MCB</b>   | 33      |
| <b>Qty per C10 MCB</b>   | 34      |
| <b>Qty per C16 MCB</b>   | 56      |
| <b>Power factor</b>      | ≥0.90   |

**Photometric data**

|                                    |            |
|------------------------------------|------------|
| <b>Color T (K)</b>                 | 3000       |
| <b>Color Rendering Index (CRI)</b> | ≥80        |
| <b>Light distribution</b>          | Asymmetric |
| <b>Efficacy (lm/W)</b>             | 121        |
| <b>Flux (lm)</b>                   | 2170       |
| <b>SDCM</b>                        | ≤3         |

**Installation data**

|                               |                      |
|-------------------------------|----------------------|
| <b>Installation (surface)</b> | Wall                 |
| <b>Cable entries</b>          | 2                    |
| <b>Connection</b>             | Terminal block 3x2.5 |
| <b>Through wiring</b>         | Yes                  |

**Technical data**

|                                         |           |
|-----------------------------------------|-----------|
| <b>IP class</b>                         | IP20      |
| <b>Ambient temp, min (°C)</b>           | +10       |
| <b>Ambient temp, max (°C)</b>           | +35       |
| <b>Calculated LED lifetime, L80 (h)</b> | 100 000   |
| <b>Driver lifetime (h)</b>              | 100 000   |
| <b>Compliance</b>                       | CE; REACH |

**Measurements**

|                          |      |
|--------------------------|------|
| <b>Length (mm)</b>       | 1163 |
| <b>Height/depth (mm)</b> | 75   |
| <b>Width (mm)</b>        | 55   |
| <b>Net weight (kg)</b>   | 3.2  |

