
**Sevede WA L1200 Asym 18W 2200
ActiveAhead-2 840 White**

Article number 26908402256



Product feature

Wireless controls	ActiveAhead
Technology	BT Mesh
Driver type	Freedom
Sensor type	PIR
Material of housing	Aluminium (Recycled)
Diffuser/optics	Opal
Color of reflector	White
Light source	Integrated LED
Color of housing	White
RAL	9016
Gtin	7333160038471

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	18
Standby power (W)	0.5
Qty per B16 MCB	33
Qty per C10 MCB	34
Qty per C16 MCB	56
Power factor	≥0.90

Photometric data

Color T (K)	4000
Color Rendering Index (CRI)	≥80
Light distribution	Asymmetric
Beam description	Very wide
Efficacy (lm/W)	126
Flux (lm)	2270
SDCM	≤3

Installation data

Installation (surface)	Wall
Cable entries	2
Connection	Terminal block 3x2.5
Through wiring	Yes

Technical data

IP class	IP20
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+35
Calculated LED lifetime, L80 (h)	100 000
Driver lifetime (h)	100 000
Compliance	CE; REACH

Measurements

Length (mm)	1163
Height/depth (mm)	75
Width (mm)	55
Net weight (kg)	3.2

