

**Safie RE D190 MI 2100 On/Off 840  
White CWP-2,5m**

Article number 60628402100



**Product feature**

<b>Driver type</b>	On/off
<b>Material of housing</b>	Aluminium
<b>Diffuser/optics</b>	Reflector
<b>Color of reflector</b>	Mirror
<b>Light source</b>	Integrated LED
<b>Color of housing</b>	White
<b>RAL</b>	9016
<b>Gtin</b>	7333160037740

**Installation data**

<b>Mounting</b>	Recessed; Surface
<b>Cable entries</b>	1
<b>Connection</b>	2.5 m cable with plug
<b>Cut out (mm)</b>	160

**Lifetime**

<b>Calculated LED lifetime, L70 (h)</b>	100 000
<b>Calculated LED lifetime, L80 (h)</b>	100 000

**Measurements**

<b>Height/depth (mm)</b>	61
<b>Diameter (mm)</b>	190
<b>Net weight (kg)</b>	0.5

**Photometric data**

<b>Color T (K)</b>	4000
<b>Color Rendering Index (CRI)</b>	≥80
<b>Beam angle (°)</b>	60
<b>Beam description</b>	Medium
<b>Unified Glare Rating (UGR)</b>	≤19
<b>Efficacy (lm/W)</b>	147
<b>Flux (lm)</b>	2200
<b>SDCM</b>	≤3

**Technical data**

<b>IP class</b>	IP20; IP54
<b>Ambient temp, min (°C)</b>	+10
<b>Ambient temp, max (°C)</b>	+40
<b>Compliance</b>	ErP; CE; REACH; RoHS
<b>Guarantee (years)</b>	5

**Electrical data**

<b>Frequency (Hz)</b>	50-60
<b>Voltage (V)</b>	220-240
<b>Isolation</b>	Class 2
<b>Power (W)</b>	Adjustable
<b>Qty per B16 MCB</b>	45
<b>Qty per C10 MCB</b>	47
<b>Qty per C16 MCB</b>	75
<b>Power factor</b>	≥0.90

