
**Cellini Panel RE 595x595 32W
3200 DALI 930 Black**

Article number 30329303220



Product feature

Driver type	DALI-2
Material of housing	Aluminium; Steel
Material of diffuser/optics	Polystyrene (PS)
Diffuser/optics	Lens; Microprismatic
Color of reflector	Black
Light source	Integrated LED
Color of housing	White
RAL	9003

Installation data

Mounting	Recessed
Looping	Yes
Length cable (m)	2.5
Material cable	Plastic non-PVC

Lifetime

Calculated LED lifetime, L70 (h)	100 000
Calculated LED lifetime, L80 (h)	76 000
Driver lifetime (h)	100 000

Measurements

Length (mm)	595
Height/depth (mm)	50
Width (mm)	595
Net weight (kg)	3.1

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥90
Light distribution	Direct
Beam description	Medium
Unified Glare Rating (UGR)	≤16
Efficacy (lm/W)	95
Flux (lm)	3040
SDCM	≤3

Technical data

IP class	IP20
IK class	IK03
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+30
Compliance	CE; REACH

Electrical data

Frequency (Hz)	50-60
Voltage (V)	220-240
Isolation	Class 2
Power (W)	32
Standby power (W)	0.3
Qty per B16 MCB	66
Qty per C10 MCB	68
Qty per C16 MCB	111
Power factor	≥0.90

