

13091001

Auxiliary contact - separate common points



1 NO/NC contact block for positions I, 0 and II.

General characteristics

- Separate common points & linked common points.
- Easy and fast integration on ATyS M.
- A maximum of two auxiliary contact blocks can be fitted to each product.
- Each auxiliary contact block integrates 3 NO/NC auxiliary contacts (I, 0, II).

Access to resources (ex: manuals)

Technical Characteristics

Number change-over contacts	3
Number NC contacts	3
Number NO contacts	3
Type	Separate common

Classification

UNSPSC	39122205
ETIM Class	EC000041
IGCC	5177

Commerce

Effective date	2018-11-20
Offer Life Cycle Code	40
Country of origin	TN

ETIM - Electrical characteristics

Number of contacts as normally open contact	3
Number of contacts as normally closed contact	3
Rated operation current Ie at AC-15, 230 V [A]	2

ETIM - Mechanical characteristics

Type of electric connection	Spring clamp connection
Mounting method	Side mounting

ETIM - Technical features

Model	Integrable
Lamp holder	None

Logistics

GTIN/EAN	3596033039829
Customs number	8536500700
Price unit	PC
Weight of the packing unit [kg]	0.067
Length of the packing unit [m]	0.02
Width of the packing unit [m]	0.19
Depth of the packing unit [m]	0.12

Norms

Conformity to standards	CCC IEC
-------------------------	-------------