
Glomma IP65 CE L1200 On/Off 840

Article number 57128405000



Product feature

Driver type	On/off
Material of housing	Polycarbonate
Material of diffuser/optics	Polycarbonate (PC)
Diffuser/optics	Opal
Light source	Integrated LED
Gtin	7333160039829

Installation data

Cable entries	2
Connection	Terminal block 3x2.5
Through wiring	Yes
Through wiring cross section (mm²)	3x2.5

Lifetime

Calculated LED lifetime, L70 (h)	>100 000
Calculated LED lifetime, L80 (h)	100 000
Calculated LED lifetime, L90 (h)	50 000
CLO function	No
Driver lifetime (h)	100 000

Measurements

Length (mm)	1200
Height/depth (mm)	54
Width (mm)	66
Net weight (kg)	0.89

Photometric data

Color T (K)	4000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam angle (°)	120
Beam description	Wide
Efficacy (lm/W)	150
Flux (lm)	4950
SDCM	≤3

Technical data

IP class	IP65
IK class	IK08
Ambient temp, min (°C)	-20
Ambient temp, max (°C)	+45
Compliance	CE; REACH; D-mark

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 2
Power (W)	Adjustable
Available wattages (W)	17; 25; 33
Qty per B16 MCB	56
Qty per C10 MCB	35
Qty per C16 MCB	56
Power factor	≥0.90

