

48250405

Multifunction meter DIRIS A-30 12-48VDC



Strong points

- Easy to use
- Detects wiring errors
- Customisable
- Compliant with IEC 61557-12

General characteristics

- Easy to use.
- Detects wiring errors.
- Customisable.
- Webserver function.
- Compliant with IEC 61557-12.

Compliance with standards

- IEC 61557-12
- IEC 62053-22 Class 0.5 S
- IEC 62053-23 Class 2
- UL

Access to resources (ex: manuals)

The DIRIS A-30 is a power monitoring device that provides the user with all of the measurements needed to complete energy efficiency projects and to assure the monitoring of electrical distribution.

All the information can be used and analysed remotely using energy efficiency software packages.

Technical Characteristics

Application	Analysis
Communication ports	Optional RS485 or Ethernet
Communication protocols	Optional Modbus RTU, TCP or Profibus
Model	A-30
Type	12-48VDC

Classification

UNSPSC	83101808
ETIM Class	EC002301
IGCC	6042

Commerce

Effective date	2017-12-01
Offer Life Cycle Code	40
Country of origin	TN

ETIM - Technical features

Ampere meter	Yes
Blind power meter	Yes
With rotational speed meter	No
Frequency meter	Yes
Pulse counter	Yes
Voltmeter	Yes
Effective power measurement device	Yes

Logistics

GTIN/EAN	3596033014864
Customs number	9030310090
Price unit	PC
Weight of the packing unit [kg]	0.48
Length of the packing unit [m]	0.12
Width of the packing unit [m]	0.11
Depth of the packing unit [m]	0.11

Norms

Conformity to standards	IEC UL
-------------------------	------------