

50317012

Hexagonal insulator Height 70 M12 female to female

With SOCOMEC's insulating bar supports you can:

- mount and attach the busbars inside the electrical panel,
- cope with the forces experienced by the busbars during a short circuit

Strong points

- Insulating materials
- Durability
- Adaptability

General characteristics

- Polyester without halogen.
- UL94 VO self-extinguishing.
- Colour red RAL 3002.
- Operating temperature from -40 °C to +130 °C.
- Deformation under load temperature (ASTM D643): > 200 °C.
- Dielectric constant (ASTM D150): 4/5.
- Arc resistance (ASTM D495): > 180 s.
- Water absorption (ASTM D570):

Compliance with standards

- IEC 61439-1
- IEC 60865-1

Link to the reference



<https://emea.socomec.com/en/reference/50317012>

Classification

UNSPSC	39121321
ETIM Class	EC001166
IGCC	4462

Commerce

Effective date	2003-11-26
Offer Life Cycle Code	40
Country of origin	IN

ETIM - Electrical characteristics

Number of poles	1
-----------------	---

Logistics

GTIN/EAN	3596031724024
Customs number	8546901000
Price unit	PC
Weight of the packing unit [kg]	0.266
Length of the packing unit [m]	0.07
Width of the packing unit [m]	0.06
Depth of the packing unit [m]	0.06

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Height [mm]	70
Width [mm]	55
Depth [mm]	55
Weight [kg]	0.266
Diameter	M12
Rated voltage	2400 VAC
Type	Hexagonal