

## 48290591

## RJ12 connection cable 0.2m x6



The RJ12 connections allow you to connect modules very quickly and to automatically configure connected current sensors:

- communication address,
- load type,
- sensor type and ratio,
- automatic rating and verification of current travel direction. Wiring errors are also prevented and installation is simplified.

## General characteristics

- Plug & Play.
- Colour coded.
- Multiple lengths.

## Link to the reference

Classification	
UNSPSC	83101808
ETIM Class	EC001262
IGCC	6042
Commerce	
Effective date	2013-11-22
Offer Life Cycle Code	40
Country of origin	TH
ETIM - Mechanical characteristics	
Length [m]	0.2
Colour outer sheath	Grey
Anti-kink sleeve	None
Cable construction	Other
AWG-size	26
Cable type	U/UTP
ETIM - Technical features	
Category	5
Type of connector connection 1	RJ12 6(6)
Type of connector connection 2	RJ12 6(6)
Locking lever	No
Fire retardant version	No
Oil resistant according to EN IEC 60811-404	Yes
Pin assignment	1:1
NVP value [%]	70
Logistics	
GTIN/EAN	3596032776626
Customs number	8544429090
Price unit	PC
Weight of the packing unit [kg]	0.04
Length of the packing unit [m]	0.15
Width of the packing unit [m]	0.15
Depth of the packing unit [m]	0.015
Norms	
Conformity to standards	IEC UL
Technical Characteristics	
Length of the product unit [mm]	200
Color	Red, Black, Yellow, Blue, Green, Purple
Connector	RJ12
Length	0.2 m
Туре	Connection cable for TE, TR/iTR, TF

current sensors

2025-05-15 15:49:37