



NEW

isolating supports for busbars in XL³ cabinets and enclosures (continued)



373 73



373 75

Pack	Cat.Nos	1 C-section bar per pole
1	373 73	≤ 1 250 A Support for copper C-section bars Cat.Nos 374 60/ 61/62 and Cat.No 098 82 For mounting in XL ³ 4 000 enclosure or cable sleeves: - Horizontal busbars - Side-mounted vertical busbars - Vertical busbars at back
1	373 74	Lug support For fitting at the bottom of a vertical busbars
1	373 75	1 or 2 C-section bars per phase ≤ 2 500 A Support for 1 or 2 copper C-section bars Cat.Nos 374 60/61/62 per phase or 1 bar Cat.No 098 82 (1 single bar for the neutral) For mounting in XL ³ 4 000 enclosures or cable sleeves: - Horizontal busbars - Side-mounted vertical busbars - Vertical busbars at back
1	373 76	Lug support For fitting at the bottom of a vertical busbars
1	373 77	Accessories for C-section busbars Joining kit For joining supports Cat.Nos 373 73/74/75/76 to create busbars up to 2 000 A Connection plates For connecting C-section bars to extend a busbars or to connect vertical bars to horizontal bars
1	373 82	1 bar per phase
1	373 83	2 bars per phase

1	205 51	Fixing supports Set of 2 adjustable crosspieces Length 350 mm
1	205 52	Length 600 mm
1	205 53	Length 850 mm
1	205 31	Set of 2 crosspieces for partial chassis Length 350 mm
1	205 32	Length 600 mm
1	373 14	Extension piece For mounting busbars supports Cat.No 373 15 and Lexic distribution blocks Cat.No 373 16/17/18 in XL ³ 800 and 4 000 cabinets and enclosures

copper bars



374 19 + 373 11

Standard distribution

Pack	Cat.Nos	Copper bars
		Rigid flat
10	373 88	Cross section (mm ²) 12 x 2 Permissible I (A) 110 Threaded holes Ø mm M5 Pitch 18 Length (mm) 990
10	373 89	Cross section (mm ²) 12 x 4 Permissible I (A) 160 Threaded holes Ø mm M5 Pitch 18 Length (mm) 990
10	374 33	Cross section (mm ²) 15 x 4 Permissible I (A) 200 Threaded holes Ø mm M6 Pitch 18 Length (mm) 990
10	374 34	Cross section (mm ²) 18 x 4 Permissible I (A) IP ≤ 30 245 Threaded holes Ø mm M6 Pitch 18 Length (mm) 990
10	374 38	Cross section (mm ²) 25 x 4 Permissible I (A) IP > 30 280 Threaded holes Ø mm M6 Pitch 18 Length (mm) 990
4	374 18	Cross section (mm ²) 25 x 5 Permissible I (A) IP ≤ 30 330 Threaded holes Ø mm M6 Pitch 25 Length (mm) 1 750
4	374 19	Cross section (mm ²) 32 x 5 Permissible I (A) IP > 30 450 Threaded holes Ø mm M6 Pitch 25 Length (mm) 1 750
1	374 40	Cross section (mm ²) 50 x 5 Permissible I (A) IP ≤ 30 700 Threaded holes Ø mm 10.5 - 6.5 Pitch 25 Length (mm) 1 750
1	374 41	Cross section (mm ²) 63 x 5 Permissible I (A) IP > 30 800 Threaded holes Ø mm 10.5 - 8.5 Pitch 25 Length (mm) 1 750
1	374 59	Cross section (mm ²) 75 x 5 Permissible I (A) IP ≤ 30 950 Threaded holes Ø mm 10.5 - 6.5 Pitch 25 Length (mm) 1 750
1	374 43	Cross section (mm ²) 80 x 5 Permissible I (A) IP > 30 1 000 Threaded holes Ø mm 10.5 - 6.5 Pitch 25 Length (mm) 1 750
1	374 46	Cross section (mm ²) 100 x 5 Permissible I (A) IP ≤ 30 1 250 Threaded holes Ø mm 10.5 - 6.5 Pitch 25 Length (mm) 1 750
		C-section Length 1 780 mm, 40 x 20
1	374 60	Cross section (mm ²) 155 Permissible I (A) IP ≤ 30 500 Threaded holes Ø mm 400
1	374 61	Cross section (mm ²) 265 Permissible I (A) IP > 30 800 Threaded holes Ø mm 630
1	374 62	Cross section (mm ²) 440 Permissible I (A) IP ≤ 30 1 250 Threaded holes Ø mm 1 000
1	098 82	Cross section (mm ²) 640 Permissible I (A) IP > 30 1 450 Threaded holes Ø mm 1 250
		Flexible Supplied flat, length 2 m
1	374 10	Cross section (mm ²) 13 x 3 Permissible I (A) IP ≤ 30 200 Threaded holes Ø mm 160
1	374 67	Cross section (mm ²) 20 x 5 Permissible I (A) IP > 30 400 Threaded holes Ø mm 250
1	374 11	Cross section (mm ²) 24 x 4 Permissible I (A) IP ≤ 30 400 Threaded holes Ø mm 250
1	374 12	Cross section (mm ²) 32 x 5 Permissible I (A) IP > 30 630 Threaded holes Ø mm 400
1	374 57	Cross section (mm ²) 50 x 5 Permissible I (A) IP ≤ 30 850 Threaded holes Ø mm 630
1	374 58	Cross section (mm ²) 50 x 10 Permissible I (A) IP > 30 1 250 Threaded holes Ø mm 1 000
1/10	373 11	Accessories Isolating profile for flat copper bars 18 x 4, 25 x 4, 25 x 5 and 32 x 5 mm, length 1 m Supplied with fixing clips
10	374 64	M8 hammer head bolt for C-section bar
10	374 65	M12 hammer head bolt for C-section bar
50	347 48	Clip nuts with pins for M6 screws
50	347 49	Clip nuts with pins for M8 screws
50	367 75	M6-10 HF screws with contact washers