



**Sevede PE L1700 MP 50/50 48W
6100 ActiveAhead-2 830 White**

Article number 26218306156

Product feature

Wireless controls	ActiveAhead
Technology	BT Mesh
Driver type	Freedom
Sensor type	PIR
Material of housing	Aluminium (Recycled)
Diffuser/optics	Microprismatic
Color of reflector	White
Light source	Integrated LED
Color of housing	White
RAL	9016

Installation data

Mounting	Pendent
Cable entries	1
Connection	Cable
Length cable (m)	2.5
Material cable	Plastic non-PVC

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	48
Standby power (W)	0.5
Qty per B16 MCB	18
Qty per C10 MCB	19
Qty per C16 MCB	31
Power factor	≥0.95

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥80
Light distribution	Indirect/Direct
Distribution (Up/down)	50/50
Beam angle (°)	90
Beam description	Medium wide
Unified Glare Rating (UGR)	≤19
Efficacy (lm/W)	124
Flux (lm)	5970
SDCM	≤3

Technical data

IP class	IP20
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+35
Calculated LED lifetime, L80 (h)	100 000
Driver lifetime (h)	100 000
Compliance	CE; REACH; ENEC

Measurements

Length (mm)	1723
Height/depth (mm)	75
Width (mm)	55
Net weight (kg)	4.2

