



DATA SHEET

installation contactors

HS 2-230UC/25-22

with coil voltage 230 V AC / 220 V DC

Article number 09980450



[Internetlink](#)

Function

Installation contactors are electromagnetically operated switches. If a control current flows through the magnetic coil, the main circuit closes the magnetic energiser. As long as the control current flows, the switch-on position is maintained. If the control current is interrupted, a spring forces the disconnection or return of the contacts to their original position. This design means that contactors ensure a galvanic separation between the control circuit and the switched circuit whilst simultaneously allowing high currents to be switched. Installation contactors are only designed in a limited way for release and must be protected against overload and short-circuits by upstream protective devices. Installation contactors in the HS family for installation in distribution boards are extremely quiet and have very low-noise switching processes, are highly versatile thanks to their utilisation categories, and have prolonged mechanical and electrical service life. The magnetic coil in this family is suitable for continuous operation (100 % duty cycle). This no-noise design is suitable for use in hotels, offices and residential areas.

Features

wide range of different contacts, high electrical and mechanical endurance, suitable auxiliary switch and seal cap available

Mounting

quick fastening to mounting rail, any installation position

Applications

Installation contactors can be used in a variety of ways. The low-noise version is suitable for industry and workshops, whilst the no-noise version is suitable for hotels, offices and residential areas. They take on the switching of incandescent lamps, fluorescent lamps, transformers for halogen low-voltage lamps, mercury vapour high-pressure lamps (HQL, HPL), metal halide lamps (HQL, HPI), sodium vapour, low and high-pressure lamps, storage heaters and drives (motors).

Notes

The names of devices in this family contain both the rated current (first pair of digits) and the contact variant (last pair of digits): For example, a HS 25-31 has a rated current of 25 A, three NOCs and one NCC, At ambient temperatures of 40°C and higher, using the DHDS spacer is recommended, The HS 1 contact is 1 module width wide, and thus the HS 2 and HS 3 are 2 and 3 module widths wide.

Accessories

spacers DHDS, seal caps HSP

Technical Data

Technical Data	HS 2-230UC/25-22
Series	HS 2
	control input
Rated voltage (AC)	230 V
Rated voltage (DC)	220 V
Rated frequency	DC, 50 Hz/60 Hz
Rated power (switch on)	20 VA ... 25 VA
rated power (retaining)	3 W ... 4 W
	load circuit
Specification	switching contact
min. Contact opening	3 mm
contact assignment	2 NC/2 NO
Rated voltage (AC)	400 V

Subject to technical changes

Technical Data	HS 2-230UC/25-22
Rated current (AC)	25 A
Rated insulation voltage	440 V
Switching frequency	max. 300 / h
Allowed utilization category	AC-1, AC-2, AC-3
Power dissipation per pole AC-1	2 W
Overtoltage class	I, II, III
rated short-circuit current "r"	3 kA
rated short-circuit current "Iq"	10 kA
Rated voltage AC-1 (fix)	230 V
max. Rated power AC-1 230 V	5.7 kW
Rated voltage AC-3 one-phase (fixed)	230 V
max. Rated power AC-3 230 V	1.3 kW
max. rated power glow lamps	3000 VA
max. Rated power fluorescent lamp compensated	1360 VA
max. Rated power fluorescent lamp not compensated	1190 VA
max. rated power fluorescent lamps duo-switching	2552 VA
contact endurance AC-1	100000 switching cycles
contact endurance AC-3	150000 switching cycles
Duration of light arcs	10 ms ... 15 ms
Switching delay, open	13 ms ... 23 ms
Switching delay, close	17 ms ... 24 ms
quiet design	true
	screw-type terminal M3.5 top and bottom (load circuit)
Allowed types of wires	aluminium conductor, copper conductor, solid conductor, flexible conductor
Connection C1 Maximum number of conductors per terminal	1
Cross section solid	1-wire: 1.5 mm ² ... 10 mm ²
Connecting capacity flexible	1-wire: 1.5 mm ² ... 6 mm ²
Cross section flexible with ferrule	1.5 mm ² ... 6 mm ²
Cross section stranded	1-wire: 1.5 mm ² ... 10 mm ²
Tightening torque	0.8 Nm ... 1.4 Nm
	screw-type terminal M3 top and bottom (control input)
Allowed types of wires	aluminium conductor, copper conductor, solid conductor, flexible conductor
Connection C2 Maximum number of conductors per terminal	1
Cross section solid	1-wire: 0.75 mm ² ... 2.5 mm ²
Connecting capacity flexible	1-wire: 0.5 mm ² ... 2.5 mm ²
Cross section flexible with ferrule	0.5 mm ² ... 1.5 mm ²
Cross section stranded	1-wire: 0.75 mm ² ... 2.5 mm ²
Tightening torque	0.6 Nm ... 1.2 Nm
	General data
Duty cycle	continuous operation (Duty cycle ≤ 100 %)
Operating position	optional
Mechanical endurance	min. 10 · 10 ⁶ switching cycles
Electrical endurance	min. 1 · 10 ⁶ switching cycles
Ambient temperature	60°C when installed individually

Subject to technical changes

Technical Data	HS 2-230UC/25-22
Housing type	distribution board housing
Installation type	Mounting rail (35 mm)
Housing material	thermoplastic
Protection class	IP20
Width	36 mm
Height	85 mm
Depth	65 mm
Installation depth	60 mm
Module widths	2
Design requirements/Standards	EN 60715, EN 60947-4-1, VDE 0660-102
Degree of pollution according to EN 60664	3

Dimensions

