


Zenith

Technical datasheet




Dimensions (mm):



Installation: Keep a minimum 50 mm security distance between the luminaire and the ceiling to ensure its correct performance.

Photometric data:



Separación [m] Diámetro cónico [m] Intensidad luminosa [lx]

CD - C180 (Semiángulo de dispersión: 114.0°)

CO - C180 (Semiángulo de dispersión: 114.0°)

CO - C180 (Semiángulo de dispersión: 114.0°)

LED Panels
Ref. ZH43CSB



Recessed
Mounting




CASAMBI

LED Panels: Zenith .Manufactured in 3 assemblable parts: Diffuser polystyrene high reflection and low luminance, trim frame made of technical polycarbonate high resistance and body of galvanized steel and coated with resins, polyester with electrostatic treatment. Diffuser: Technical plastic. Light distribution: Direct. Accessories: Node and sensor with Casambi technology included Color: White.

Gross lumen output	4030 lm
Net lumen output	3506 lm
Color temperatures (K)	3000
CRI	80
Hours Life L80	100.000
Hours Life L90	50.000h
Macadam ellipses	3
Beam angle	115
Photobiological security	0
Power consumption (W)	26,4
Power (W)	24
Voltage	220-240V 50/60Hz
Power factor	0,96
Class	II
UGR	19
IP	20-54
IK	07
Weight (Kg)	2,2
Operating temperature (°C)	-20 to 40
Energy efficiency	B

* Variable UGR according to project

* Photobiological safety = 0/1: Risk free



* The manufacturer reserves the right to make changes in the design and / or technical specifications.

* Guarantee extendable to 5 years depending of the project. Consult conditions.