

**Kleva CE L1200 28W 4500 PIR
Sensor On/Off 830**

Article number 51308304517



Product feature

Driver type	On/off
Material of housing	Aluminium (Recycled)
Material of diffuser/optics	Polycarbonate (PC)
Diffuser/optics	Linear prismatic; Opal
Light source	Integrated LED
Color of housing	White
RAL	9003
Gtin	7333160041754

Light management

Sensor type	PIR
--------------------	-----

Lifetime

Calculated LED lifetime, L80 (h)	>100 000
Calculated LED lifetime, L90 (h)	100 000
Driver lifetime (h)	100 000

Electrical data

Frequency (Hz)	50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	28
Standby power (W)	0.25
Qty per B16 MCB	38
Qty per C10 MCB	39
Qty per C16 MCB	64
Power factor	≥0.90

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam description	Very wide
Efficacy (lm/W)	154
Flux (lm)	4320
SDCM	≤3

Installation data

Mounting	Surface
Cable entries	4
Connection	Terminal block 5x2.5
Looping	Yes
Through wiring	Available upon request

Technical data

IP class	IP40
IK class	IK03
Ambient temp, min (°C)	0
Ambient temp, max (°C)	+40
Compliance	CE; REACH; ENEC
Guarantee (years)	5

Measurements

Length (mm)	1185
Height/depth (mm)	66
Width (mm)	110
Net weight (kg)	2

