



Sevede PE L1200 MP 40/60 36W 4300 DALI 830 White

Article number 26118304320

Sevede is our linear premium solution for office lighting. Available in white or black and two lengths as standard. Unique is that you can create a homogeneous light line in desired length. Available in four types of optics: opal, micro prismatic, lens and lens asymmetric optics. Housing is made of at least 75% recycled aluminium - Hydro Circal - for a lower carbon footprint. Available with ActiveAhead or Casambi. Wire suspension delivered with luminaire is adjustable up to 1000mm.

Product feature

| | |
|----------------------------|---------------------|
| Driver type | DALI-2 |
| Material of housing | Recycled aluminium |
| Diffuser/optics | Microprismatic (MP) |
| Color of reflector | White |
| Light source | Integrated LED |
| Color of housing | White |
| RAL | 9016 |

Installation data

| | |
|-------------------------|-----------------|
| Mounting | Pendent |
| Cable entries | 1 |
| Connection | Cable |
| Length cable (m) | 2.5 |
| Material cable | Plastic non-PVC |

Electrical data

| | |
|--------------------------|---------|
| Frequency (Hz) | 0/50-60 |
| Voltage (V) | 220-240 |
| Isolation | Class 1 |
| Power (W) | 36 |
| Standby power (W) | 0.17 |
| Qty per B16 MCB | 55 |
| Qty per C10 MCB | 57 |
| Qty per C16 MCB | 93 |
| Power factor | ≥0.95 |

Photometric data

| | |
|------------------------------------|------------------|
| Color T (K) | 3000 |
| Color Rendering Index (CRI) | ≥80 |
| Light distribution | Direct; Indirect |
| Distribution (Up/down) | 40/60 |
| Beam angle (°) | 90 |
| Beam description | Medium wide |
| Unified Glare Rating (UGR) | ≤19 |
| Efficacy (lm/W) | 115 |
| Flux (lm) | 4150 |
| SDCM | ≤3 |

Technical data

| | |
|---|-----------------|
| IP class | IP20 |
| Ambient temp, min (°C) | +10 |
| Ambient temp, max (°C) | +35 |
| Calculated LED lifetime, L80 (h) | 100 000 |
| Driver lifetime (h) | 100 000 |
| Compliance | CE; REACH; ENEC |

Measurements

| | |
|--------------------------|------|
| Length (mm) | 1163 |
| Height/depth (mm) | 75 |
| Width (mm) | 55 |
| Net weight (kg) | 2.9 |

