

Spartan PE D269 DALI C5L-1,5m

Article number 83318919220



Product feature

Driver type	DALI-2
Material of housing	Aluminium
Material of diffuser/optics	Polycarbonate (PC)
Diffuser/optics	Adjustable lens
Light source	Integrated LED
Color of housing	Black
RAL	9017
Gtin	7333160036736

Installation data

Mounting	Pendent
Connection	5-lead cable
Length cable (m)	1.5
Material cable	Rubber

Lifetime

Calculated LED lifetime, L80 (h)	>100 000
Driver lifetime (h)	100 000

Photometric data

Color T (K)	4000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam angle (°)	65;85;105
Beam description	Medium; Medium wide; Wide
Efficacy (lm/W)	170
Flux (lm)	20450
SDCM	≤3

Technical data

IP class	IP65
IK class	IK08
Ambient temp, min (°C)	-30
Ambient temp, max (°C)	+50
Compliance	CE; REACH; RoHS; D-mark; ENEC
Guarantee (years)	5

Measurements

Height/depth (mm) 181

Diameter (mm) 269

Net weight (kg) 1.9

Electrical data

Frequency (Hz) 0/50-60

Voltage (V) 220-240

Isolation Class 1

Power (W) 120

Available wattages (W) 60; 80; 100; 120

Standby power (W) 0.5

Qty per B16 MCB 13

Qty per C10 MCB 12

Qty per C16 MCB 18

Power factor ≥ 0.95

