



Gloster PE D400 3100 DALI 830 White

Article number 21608303120

Product feature

Driver type	DALI-2
Material of housing	Steel
Material of diffuser/optics	Acrylic (PMMA)
Diffuser/optics	Opal
Light source	Integrated LED
Color of housing	White
RAL	9016
Gtin	7333160042072

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥80
Light distribution	Spherical
Beam description	Very wide
Efficacy (lm/W)	115
Flux (lm)	3000
SDCM	≤3

Installation data

Mounting	Pendent
Installation (surface)	Ceiling
Cable entries	1
Connection	Terminal block 5x2.5
Looping	No
Through wiring	No
Length cable (m)	2.5
Material cable	Fabric

Lifetime

Calculated LED lifetime, L70 (h)	100 000
Calculated LED lifetime, L80 (h)	75 000
Calculated LED lifetime, L90 (h)	40 000
Driver lifetime (h)	100 000

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	26
Available wattages (W)	12; 19; 26; 32; 39
Standby power (W)	0.5
Qty per B16 MCB	50
Qty per C10 MCB	52
Qty per C16 MCB	85
Power factor	≥0.90

Measurements

Diameter (mm)	400
Net weight (kg)	3.09

Technical data

IP class	IP20
IK class	IK08
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+50
Compliance	CE; REACH
Guarantee (years)	5

