

DPX³ 630

S2 electronic release MCCBs from 250 to 630 A



4 220 60



4 220 65



Dimensions **see e-catalogue**
Electrical characteristics **see e-catalogue**

Moulded case MCCBs for switching, control isolation and protection of low voltage electrical lines

Can be fitted with auxiliaries (p. 154)

Can be used with earth leakage modules (p. 148) or with residual current relays (p. 155)

Supplied complete with:

- fixing screws
- connection plates for bars
- insulated shields (phase barriers)

Conform to IEC 60947-2 - Sealable adjustment

Can be mounted on plate in XL³ cabinets and enclosures

Pack	Cat.Nos		MCCBs electronic release S2 - fixed version	
			Adjustment of I_r , I_{sd} , t_r , t_{sd} (p. 145) Instantaneous protection $I_f = 5$ kA Green indicator lamp Connector for test unit Logic and dynamic selectivity 4P version: adjustment of neutral on front panel	
			Breaking capacity I_{cu} 36 kA (400 V~)	
	3P	4P	I_n (A)	
1	4 220 56	4 220 61	250	
1	4 220 57	4 220 62	320	
1	4 220 58	4 220 63	400	
1	4 220 59	4 220 64	500	
1	4 220 60	4 220 65	630	
			Breaking capacity I_{cu} 50 kA (400 V~)	
1	4 220 66	4 220 71	250	
1	4 220 67	4 220 72	320	
1	4 220 68	4 220 73	400	
1	4 220 69	4 220 74	500	
1	4 220 70	4 220 75	630	
			Breaking capacity I_{cu} 70 kA (400 V~)	
1	4 220 76	4 220 81	250	
1	4 220 77	4 220 82	320	
1	4 220 78	4 220 83	400	
1	4 220 79	4 220 84	500	
1	4 220 80	4 220 85	630	
			Breaking capacity I_{cu} 100 kA (400 V~)	
1	4 220 86	4 220 91	250	
1	4 220 87	4 220 92	320	
1	4 220 88	4 220 93	400	
1	4 220 89	4 220 94	500	
1	4 220 90	4 220 95	630	

Pack	Cat.Nos		MCCBs electronic release S2 with energy metering central unit - fixed version	
			Adjustment of I_r , I_{sd} , t_r , t_{sd} (p. 145) Instantaneous protection $I_f = 5$ kA Green indicator lamp Connector for test unit Logic and dynamic selectivity 4P version: adjustment of neutral on front panel	
			Breaking capacity I_{cu} 36 kA (400 V~)	
	3P	4P	I_n (A)	
1	4 220 96	4 221 01	250	
1	4 220 97	4 221 02	320	
1	4 220 98	4 221 03	400	
1	4 220 99	4 221 04	500	
1	4 221 00	4 221 05	630	
			Breaking capacity I_{cu} 50 kA (400 V~)	
1	4 221 06	4 221 11	250	
1	4 221 07	4 221 12	320	
1	4 221 08	4 221 13	400	
1	4 221 09	4 221 14	500	
1	4 221 10	4 221 15	630	
			Breaking capacity I_{cu} 70 kA (400 V~)	
1	4 221 16	4 221 21	250	
1	4 221 17	4 221 22	320	
1	4 221 18	4 221 23	400	
1	4 221 19	4 221 24	500	
1	4 221 20	4 221 25	630	
			Breaking capacity I_{cu} 100 kA (400 V~)	
1	4 221 26	4 221 31	250	
1	4 221 27	4 221 32	320	
1	4 221 28	4 221 33	400	
1	4 221 29	4 221 34	500	
1	4 221 30	4 221 35	630	



Dimensions
see e-catalogue

