

Safie RE D228 MI 2500 DALI 830 White C4L-3m

Article number 60638302520



Product feature

Driver type	DALI-2
Material of housing	Aluminium
Diffuser/optics	Reflector
Color of reflector	Mirror
Light source	Integrated LED
Color of housing	White
RAL	9016
Gtin	7333160037788

Installation data

Mounting	Recessed; Surface
Cable entries	1
Connection	3 m 4-lead cable
Cut out (mm)	200

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥80
Beam angle (°)	60
Beam description	Medium
Unified Glare Rating (UGR)	≤19
Efficacy (lm/W)	142
Flux (lm)	2410
SDCM	≤3

Technical data

IP class	IP20; IP54
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+40
Calculated LED lifetime, L70 (h)	100 000
Calculated LED lifetime, L80 (h)	100 000
Compliance	ErP; CE; REACH; RoHS
Guarantee (years)	5

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 2
Power (W)	17
Standby power (W)	0.5
Type Of Connection	Push-in terminal
Qty per B16 MCB	112
Qty per C10 MCB	70
Qty per C16 MCB	112
Power factor	≥ 0.90

Measurements

Height/depth (mm)	61
Diameter (mm)	228
Net weight (kg)	0.5

