

**57035004**

## RM cylind. fuse holder without sign. aux. cont.-100A-3PP+N-NFC-Fuse 22x58



### Strong points

- Improved safety
- High breaking capacity
- Format and specific accessories

### General characteristics

- Improved safety.
- High breaking capacity.
- Features and options.

### Compliance with standards

- IEC 60269-2,-1
- IEC 60269-1
- IEC 60269-2
- UL E307648

### Access to resources (ex: manuals)

RMs are modular fuse disconnect switches for cylindrical fuses. They ensure safe disconnection and protection against surges and short-circuits in any low voltage electrical circuit.

### Technical Characteristics

Length of the product unit [mm]	126.5
Width of the product unit [mm]	143
Depth of the product unit [mm]	76.5
Weight [kg]	0.74
Fuse melting indicator	no
Fuse size	22x58
Number of poles	3+N
Rated current [A]	100
Size	RM/RMS 100

### Classification

UNSPSC	39121624
ETIM Class	EC002705
IGCC	4974

### Commerce

Effective date	2012-06-25
Offer Life Cycle Code	40
Country of origin	ES

### ETIM - Electrical characteristics

Nominal voltage [V]	690
Number of poles	4
Concurrently switching neutral conductor	Yes

### ETIM - Mechanical characteristics

Mounting method	DIN rail
For fuse size	22x58 mm
Width in number of modular spacings	1
Built-in depth [mm]	49.5
Degree of protection (IP)	IP2X

### ETIM - Technical features

Lockable	Yes
With optical defect indication	No

### Logistics

GTIN/EAN	3596032687090
Customs number	8536109090
Price unit	PC
Weight of the packing unit [kg]	0.74
Length of the packing unit [m]	0.135
Width of the packing unit [m]	0.085
Depth of the packing unit [m]	0.16

### Norms

Conformity to standards	IEC UL
-------------------------	------------