

HRC cartridge fuses



Technical data and dimensions (p. 102-103)

Pack	Cat.Nos		Cylindrical type gG			Pack	Cat.Nos		Cylindrical type aM (motor rated)					
			Conform to NF C 63-210/211 - EN 60269-1 and 2 and IEC 60269-1, 2 and 2-1 Veritas approved				Conform to NF C 60-200 - EN 60269-1 IEC 60269-1 Veritas approved							
			Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps)		Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps)					
			Without indicator	With indicator	10 x 38 HRC				Without indicator	With indicator	8.5 x 31.5			
			10	133 94	0.5				10	120 01	1			
			10	133 01	1				10	120 02	2			
			10	133 02	134 02		2		10	120 04	4	400	20 000	
			10	133 04	134 04		4		10	120 06	6			
			10	133 06	134 06		6		10	120 08	8			
			10	133 08	134 08		8	500	100 000	10	120 10	10		
			10	133 10	134 10		10							
			10	133 12	134 12		12							
			10	133 16	134 16		16							
			10	133 20	134 20		20							
			10	133 25	134 25		25							
							14 x 51 HRC							
			10	143 02	2				10	130 92	0.25			
			10	143 04	4				10	130 95	0.50			
			10	143 06	145 06		6		10	130 01	1			
			10	143 10	145 10		10		10	130 02	2			
			10	143 16	145 16		16	500	100 000	10	130 04	4	500	100 000
			10	143 20	145 20		20			10	130 06	6		
			10	143 25	145 25		25			10	130 08	8		
			10	143 32	145 32		32			10	130 10	10		
			10	143 40	145 40		40			10	130 12	12		
			10	143 50 ⁽¹⁾	145 50 ⁽¹⁾		50			10	130 16	16		
			22 x 58 HRC			10	130 20 ⁽²⁾	20	400					
						10	130 25 ⁽²⁾	25	400					
10	153 04	4												
10	153 06	6				10	140 02	141 02	2					
10	153 10	10				10	140 04	141 04	4					
10	153 16	16				10	140 06	141 06	6					
10	153 20	20				10	140 08	141 08	8					
10	153 25	155 25	25	500	100 000	10	140 10	141 10	10					
10	153 32	155 32	32			10	140 12	141 12	12	500				
10	153 40	155 40	40			10	140 16	141 16	16					
10	153 50	155 50	50			10	140 20	141 20	20					
10	153 63	155 63	63			10	140 25	141 25	25					
10	153 80	155 80	80			10	140 32	141 32	32					
10	153 96	155 96	100			10	140 40	141 40	40					
10	153 97 ⁽¹⁾	155 97 ⁽¹⁾	125	400		10	140 45 ⁽¹⁾	141 45 ⁽¹⁾	45	400				
						10	140 50 ⁽¹⁾	141 50 ⁽¹⁾	50	400				
						10	150 25	151 25	25					
						10	150 32	151 32	32					
						10	150 40	151 40	40	500				
						10	150 50	151 50	50	100 000				
						10	150 63	151 63	63					
						10	150 80	151 80	80					
						10	150 96	151 95	100					
						10	150 97	151 97	125	400				



Isolating fuse carriers 8.5 x 31.5 and 10 x 38

see p. 133

Neutral links

10	123 00	8.5 x 31.5
10	133 00	10 x 38
10	143 00	14 x 51
10	153 00	22 x 58

(1) Overrating described by standards
(2) Overrating not described by standards

