

Tilia CE L1320 PC 7000 On/Off DS 840

Article number 57138407000



Product feature

Driver type	On/off
Material of housing	Aluminium
Material of diffuser/optics	Polycarbonate (PC)
Diffuser/optics	Opal
Light source	Integrated LED
RAL	9006
Gtin	7333160038822

Installation data

Mounting	Surface
Installation (surface)	Wall
Cable entries	2+2
Connection	Terminal block 5x2.5
Looping	Yes
Through wiring	Yes
Through wiring cross section (mm²)	5x2.5

Photometric data

Color T (K)	4000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam angle (°)	120
Beam description	Very wide
Unified Glare Rating (UGR)	≤28
Efficacy (lm/W)	140
Flux (lm)	7000
SDCM	≤3

Technical data

IP class	IP66
IK class	IK10
Corrosion class	C3
Ambient temp, min (°C)	-20
Ambient temp, max (°C)	+45
Compliance	CE; REACH
Guarantee (years)	5

Lifetime

Calculated LED lifetime, L70 (h) >100 000

Calculated LED lifetime, L80 (h) 100000

CLO function No

Driver lifetime (h) 100 000

Measurements

Length (mm) 1320

Height/depth (mm) 73

Net weight (kg) 2.41

Width (mm) 84

Electrical data

Frequency (Hz) 0/50-60

Voltage (V) 220-240

Isolation Class 1

Power (W) Adjustable 50W<

Available wattages (W) 28 (4090lm); 36 (5200lm); 42 (6000lm); 50 (7000lm)

Qty per B16 MCB 16

Qty per C10 MCB 17

Qty per C16 MCB 27

Power factor ≥ 0.95

