




Circuit breaker box



Mi 1281

- 6 modules: 1 x 6 x 18 mm
- for miniature circuit breakers (MCB)





- 1-row
- with 1-pole main branch terminal for copper conductors
- PEN 2 x 25 mm², 2 x 16 mm², Cu, round conductors
- protection cover can be sealed, with lockable cover strip
- lid fasteners for hand operation
- material: PC (polycarbonate)
- protection class: II
- colour: grey, RAL 7035


width	300 mm
height	300 mm
depth	170 mm
weight	2,566 kg

Drawings

Dimension drawing




Box walls



Operating and ambient conditions


Application area	<p>Suitable for indoor installation and outdoor installation, protected against weather influences</p> <p>However, pay attention to the climatic effects on the installed equipment , for example, high or low ambient temperatures or</p>
------------------	--

Circuit breaker box



Mi 1281

- 6 modules: 1 x 6 x 18 mm
- for miniature circuit breakers (MCB)



	formation of condensed water see technical information
Resistant to occasional cleaning procedures (direct jet)	Resistance to occasional cleaning procedures (direct jet) with high-pressure cleaner without cleaning additives, water pressure: max 100 bar, water temperature: Max. 80° C, distance => 0.15 m, in accordance with IP 69 requirements, single enclosure without lid equipment (no enclosure assembly), enclosure and cable glands at least IP 65.
Ambient temperature	Average value over 24 hours + 35 °C Maximum value + 40 °C Minimum value - 5 °C
Relative humidity	50% at 40° C short-time 100% at 25° C
Fire protection in the event of internal faults	Demands placed on electrical devices from standards and laws Minimum requirements - Glow wire test in accordance with IEC 60695-2-11: - 650°C for boxes and cable glands - 850°C for parts of insulating material necessary to retain current carrying parts in position
Burning behaviour	Glow wire test IEC 60695-2-11: 960 °C UL Subject 94: V-2 flame-retardant self-extinguishing
Degree of protection against mechanical load	IK08 (5 Joule)
Toxic behaviour	halogen-free silicone-free "halogen-free" in accordance with the examination of the cables and insulated wires - corrosiveness of fumes - as per IEC 60754-2
Note:	For material properties see technical data.