

Osmoz separate units: non-illuminated heads control and signalling units

NEW


Supplied with a fixing ring
IP 66 except Cat.Nos 238 11/12/13 - IP 67
Conform to IEC 60947-5-1

Spring return

Pack	Cat.Nos	
		Flush
10	238 00	○ White
10	238 01	● Red
10	238 02	● Green
10	238 03	● Blue
10	238 04	● Yellow
10	238 06	● Black
1	238 08	● Red engraved "O"
1	238 09	● Green engraved "I"
		Flush with shroud
5	238 11	● Red
5	238 12	● Green
5	238 13	● Black
		Projecting Ø22
5	238 21	● Red
1	238 22	● Green
5	238 26	● Black
		Mushroom head Ø40
10	238 34	● Red
10	238 35	● Green
10	238 36	● Black
1	238 37	● Yellow

Twin touch

5	239 80	Red engraved "O", green engraved "I"
5	239 82	Flush/Flush - Green/Red - IP 66
5	239 84	Flush/Projecting - Green/Red - IP 66
		Flush/Projecting - Green/Red - IP 67

Stay-put mushroom heads

		Push-pull emergency stop
10	238 72	● Red - Ø40
1	238 76	● Black - Ø40
		Push-pull EN 418 emergency stop
10	238 74	● Red - Ø40
1	238 94	● Red - Ø54
		With flag indicator "O - I"
5	238 95	● Red - Ø54
		With flag indicator "STOP - I"
		Push-turn emergency stop
10	238 80	● Red - Ø32
1	238 81	● Black - Ø32
10	238 82	● Red - Ø40
1	238 83	● Black - Ø40
		Push-turn EN 418 emergency stop
10	238 85	● Red - Ø40
		Emergency stop with key
10	238 91	● Red - Ø40
		EN 418 emergency stop with key
1	238 92	● Red - Ø40

Selector switches

With standard handle

Pack	Cat.Nos		Positions
1	239 01	● Red	2 stay-put positions - 45°
1	239 02	● Green	
10	239 03	● Black	
1	239 04	● Grey	
1	239 05	● Red	2 stay-put positions - 45°
1	239 06	● Green	
10	239 07	● Black	
1	239 08	● Grey	
1	239 09	● Black	2 positions with spring-return - 45°
1	239 13	● Black	2 positions with spring-return - 45°
10	239 15	● Black	2 stay-put positions - 90°
1	239 18	● Black	2 stay-put positions - 90°
1	239 21	● Red	3 stay-put positions - 45°
1	239 22	● Green	
10	239 23	● Black	
1	239 24	● Grey	
1	239 26	● Black	3 positions with spring-return from left to 0 - 45°
1	239 27	● Black	3 positions with spring-return from right to 0 - 45°
5	239 28	● Black	3 positions with spring-return to 0 - 45°
1	239 29	● Black	3 stay-put positions - 90°