

Safie RE D90 MI 400 DALI DTW C4L-3m White

Article number 60689000420



Product feature

Driver type	DALI-2
Material of housing	Aluminium
Material of diffuser/optics	Polycarbonate (PC)
Diffuser/optics	Reflector
Color of reflector	Mirror
Light source	Integrated LED
Color of housing	White
RAL	9016
Gtin	7333160041099

Installation data

Mounting	Recessed
Installation (surface)	Ceiling
Cable entries	1
Connection	Terminal block 3x1.5
Through wiring	Yes
Length cable (m)	3
Material cable	Plastic; Halogen free
Cut out (mm)	68;83

Photometric data

Color T (K)	Dim to warm
Color Temp Range	2000K - 3000K
Color Rendering Index (CRI)	≥95
Light distribution	Direct
Beam angle (°)	36
Beam description	Medium narrow
Unified Glare Rating (UGR)	≤25
Efficacy (lm/W)	50
Flux (lm)	400
SDCM	≤3

Technical data

IP class	IP54
Ambient temp, min (°C)	-20
Ambient temp, max (°C)	+45
Calculated LED lifetime, L70 (h)	84 000
Calculated LED lifetime, L80 (h)	54 000
Driver lifetime (h)	100 000
CLO function	No
Compliance	ErP; CE; REACH; RoHS
Guarantee (years)	5

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 2
Power (W)	8
Type Of Connection	Push-in terminal
Qty per B16 MCB	119
Qty per C10 MCB	74
Qty per C16 MCB	119
Power factor	≥ 0.90

Measurements

Diameter (mm)	90
Net weight (kg)	0.5

