

Safie RE D190 MP 1500 DALI White C4L-3m

Article number 60608901520



Product feature

Driver type	DALI-2
Material of housing	Aluminium
Material of diffuser/optics	Polycarbonate (PC)
Diffuser/optics	Microprismatic
Color of reflector	White
Light source	Integrated LED
Color of housing	White
RAL	9016
Gtin	7333160036651

Photometric data

Color T (K)	3000; 4000; 5700
Color Rendering Index (CRI)	≥80
Beam angle (°)	85
Beam description	Medium wide
Unified Glare Rating (UGR)	≤22
Efficacy (lm/W)	102
Flux (lm)	1630
SDCM	3

Installation data

Mounting	Recessed; Surface
Cable entries	1
Connection	3 m 4-lead cable
Cut out (mm)	160

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 2
Power (W)	16
Available wattages (W)	9; 11; 14; 16
Standby power (W)	0.5
Type Of Connection	Push-in terminal
Qty per B16 MCB	112
Qty per C10 MCB	70
Qty per C16 MCB	112
Power factor	≥0.90

Measurements

Height/depth (mm)	53
Diameter (mm)	190
Net weight (kg)	0.5

Technical data

IP class	IP20; IP54
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+40
Calculated LED lifetime, L70 (h)	> 100 000
Calculated LED lifetime, L80 (h)	> 100 000
Calculated LED lifetime, L90 (h)	> 100 000
Driver lifetime (h)	100 000
Compliance	CE; REACH
Guarantee (years)	5

