
**Ceos ECO PE L1200 MP 30/70 4000
DALI 840 White**

Article number 29008404020



Product feature

Driver type	DALI-2
Material of housing	Aluminium (Recycled)
Material of diffuser/optics	Acrylic (PMMA)
Diffuser/optics	Microprismatic
Light source	Integrated LED
Color of housing	White
RAL	9016

Installation data

Mounting	Pendent
Cable entries	1
Connection	Cable
Length cable (m)	2.5
Material cable	Plastic non-PVC

Lifetime

Calculated LED lifetime, L80 (h)	>100 000
Calculated LED lifetime, L90 (h)	>100 000
Driver lifetime (h)	100 000

Measurements

Length (mm)	1226
Height/depth (mm)	65
Width (mm)	65
Net weight (kg)	2.2

Photometric data

Color T (K)	4000
Color Rendering Index (CRI)	≥80
Light distribution	Indirect/Direct
Distribution (Up/down)	30/70
Beam angle (°)	90
Beam description	Medium wide
Unified Glare Rating (UGR)	19
Efficacy (lm/W)	154
Flux (lm)	4150
SDCM	≤3

Technical data

IP class	IP20
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+35
Compliance	CE
Guarantee (years)	5

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	27
Standby power (W)	0.3
Qty per B16 MCB	55
Qty per C10 MCB	57
Qty per C16 MCB	93
Power factor	≥0.95

