

47290603

Power supply P30 100-240 VAC / 24 VDC 30 W

Strong points

- Easy mounting
- Reliable
- Redundancy

General characteristics

- 100-240 VAC input.
- 2 x 24 VDC output terminals.
- DIN-rail mounted.

Compliance with standards

- EN 60204-1 / Overvoltage category III
- IEC 60950-1 (SELV) and EN 60204-1 (PELV)
- UL/C-UL listed UL 508
- UL/C-UL Recognized UL 60950
- NEC Class 2 as per UL 1310

Access to resources (ex: manuals)

The 24 VDC Power supplies are used for DIRIS Digiware & ISOM Digiware power & insulation monitoring systems.

The power supplies are connected to system interfaces (D-xx display, M-xx gateway or C-31 interface) which in turn power the entire system thanks to the Digiware bus.

Technical Characteristics

Model	P30
Output power	30 W
Output voltage	24 Vdc
Input voltage	100-240 Vac

Classification

UNSPSC	83101808
ETIM Class	EC002542
IGCC	6042

Commerce

Effective date	2018-10-01
Offer Life Cycle Code	40
Country of origin	VN

ETIM - Electrical characteristics

3rd secondary output voltage AC [V]	24..24
Max. output current 1 [A]	30
Rated supply voltage DC [V]	54..54
Power consumption [VA]	61

Logistics

GTIN/EAN	3596033012631
Customs number	9031900000
Price unit	PC
Weight of the packing unit [kg]	0.23
Length of the packing unit [m]	0.105
Width of the packing unit [m]	0.07
Depth of the packing unit [m]	0.075