

## 192T2010

### Sensor TCA 21 Current Transformer Solid core 100A class 0.5



#### Strong points

- Compatible accuracy class
- Wide range of ratings and dimensions
- Quick and easy to install

#### General characteristics

- Accuracy class: 0.2s — 0.5 or 1.
- Dielectric quality: 3 kV — 50 Hz — 1 min.
- Operating frequency: 50 — 60 Hz.
- Permanent overload: 1.2 In.
- Insulation class: E (120 °C).

#### Compliance with standards

- IEC 61869-2
- IEC 61439-1

#### Access to resources (ex: manuals)

Current transformers deliver to the secondary a standard current proportional to the primary current and adapted to the rating of the associated device. They are equipped as standard with removable terminal covers and double terminals allowing the secondary to be short-circuited without any risk.

They are mounted using two screw-on metal brackets or, in certain cases, by a clip-on DINrail fastener. The connections are made by screws or by fast-on terminals.

#### Technical Characteristics

Model	TCA 21
Opening	Diam.21
Rated current [A]	100
Secondary rated current	5
Function	Current measurement
Type of current	AC
Type of product	Solid core
Internal diameter	21
Secondary Output	Current
Accuracy class	0.5
Type of connection	Terminal block
Conformity to standards	IEC 61869-2
Customisable	No

#### Classification

UNSPSC	39121032
ETIM Class	EC002048
IGCC	4186

#### Commerce

Description	Current Transformers TCA 21 primary 100A/secondary 5A class 0.5, diameter 21mm, current transformers deliver to the secondary a standard current proportional to the primary current and adapted to the rating of the associated device
Effective date	1998-02-09
Offer Life Cycle Code	40
Country of origin	DE

#### ETIM - Electrical characteristics

Rated primary current [A]	100
Rated secondary current [A]	5
Rated secondary apparent power [VA]	1.5
Accuracy class	0.5
Overcurrent limiting factor	FS 5
Calibrated	No

#### ETIM - Mechanical characteristics

With contact protection	No
Opening diameter [mm]	21
Snap mounting	Yes
With copper rail	Yes
Secondary connection	Screw connection

### ETIM - Technical features

Model	Through-feed current converter
Number of primary inputs	1

### Logistics

GTIN/EAN	3596031090846
Customs number	8504312990
Price unit	PC
Weight of the packing unit [kg]	0.19
Length of the packing unit [m]	0.083
Width of the packing unit [m]	0.05
Depth of the packing unit [m]	0.055

### Norms

Conformity to standards	IEC
-------------------------	-----