

Kleva CE L1200 42W 6600 DALI 830

Article number 51308306620



Product feature

Driver type	DALI-2
Material of housing	Aluminium (Recycled)
Material of diffuser/optics	Polycarbonate (PC)
Diffuser/optics	Linear prismatic; Opal
Light source	Integrated LED
Color of housing	White
RAL	9003
Gtin	7333160038280

Installation data

Mounting	Surface
Cable entries	6
Connection	Terminal block 5x2.5
Looping	Yes
Through wiring	Available upon request

Lifetime

Calculated LED lifetime, L90 (h)	100 000
Driver lifetime (h)	100 000

Measurements

Length (mm)	1185
Height/depth (mm)	66
Width (mm)	110
Net weight (kg)	2

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam description	Very wide
Unified Glare Rating (UGR)	<25
Efficacy (lm/W)	152
Flux (lm)	6380
SDCM	≤3

Technical data

IP class	IP44
IK class	IK07
Ambient temp, min (°C)	-25
Ambient temp, max (°C)	+40
Compliance	CE; REACH; ENEC
Guarantee (years)	5

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	42
Standby power (W)	0.17
Qty per B16 MCB	28
Qty per C10 MCB	29
Qty per C16 MCB	47
Power factor	≥0.95

