



NZ KL 54



- Hinged flap

CONNECTION DATA

MECHANICAL PROPERTIES

Delivered accessories:	Fastening material
IP degree of protection:	IP54
Sealable without accessories:	Yes
	Lid sealable without further accessories
Maximum bracket diameter:	6 mm

AMBIENT CONDITIONS

Application area:	Indoor installation
Maximum ambient temperature 24 h:	35 °C
Ambient temperature:	-5 °C up to +40 °C
Relative humidity:	≤ 50 % at 40 °C, ≤ 100 % at 25 °C

DIMENSIONS

Height: 358 mm
Width: 190 mm
Depth: 23 mm
Net weight: 0.402 kg

CERTIFICATES

conforming to the standards: DIN EN IEC 61439-2, DIN 43870

SALES DATA

Product number: 2000055
EAN: 4012591650553
Pack unit: 1
Customs tariff number: 85371098
ETIM class: DYNAMIC: EC002527 - Window (enclosure/cabinet)
ETIM-4.0: EC002527 - Window (enclosure/cabinet)
ETIM-5.0: EC002527 - Window (enclosure/cabinet)
ETIM-6.0: EC002527 - Window (enclosure/cabinet)
ETIM-7.0: EC002527 - Window (enclosure/cabinet)

TENDER TEXT

Standard meter hinged window NZ KL 54, according to DIN 43870, standard opening size 140 x 310 mm, for tool or hand operation, IP 54

DRAWINGS

