



Samo RE D230 34W 3800 DALI 840 60°

Article number 60128403720

Product feature

Driver type	DALI-2
Material of housing	Aluminium
Material of diffuser/optics	Aluminium
Diffuser/optics	Lens
Color of reflector	White
Light source	Integrated LED
Color of housing	White
RAL	9010

Installation data

Mounting	Recessed
Installation (surface)	Ceiling
Length cable (m)	2.5
Cut out (mm)	177-203

Lifetime

Calculated LED lifetime, L70 (h)	> 100 000
Calculated LED lifetime, L80 (h)	> 100 000
Driver lifetime (h)	100 000

Photometric data

Color T (K)	4000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam angle (°)	60
Beam description	Medium
Unified Glare Rating (UGR)	≤19
Efficacy (lm/W)	112
Flux (lm)	3800
SDCM	≤3

Technical data

Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+25
Compliance	CE; REACH

Measurements

Height/depth (mm) 128

Diameter (mm) 230

Net weight (kg) 0.8

Electrical data

Frequency (Hz) 50-60

Voltage (V) 220-240

Isolation Class 2

Power (W) 34

Standby power (W) 0.3

Qty per B16 MCB 66

Qty per C10 MCB 68

Qty per C16 MCB 111

Power factor ≥ 0.90

