

**Sevede RE L1250 OP 46W 5000
DALI 840 White**

Article number 36628405020



Product feature

Driver type	DALI-2
Material of housing	Aluminium (Recycled)
Diffuser/optics	Opal
Color of reflector	White
Light source	Integrated LED
Color of housing	White
RAL	9016

Installation data

Mounting	Recessed
Connection	Cable
Length cable (m)	2.5
Material cable	Halogen free

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	46
Standby power (W)	0.17
Qty per B16 MCB	28
Qty per C10 MCB	29
Qty per C16 MCB	47
Power factor	≥0.95

Photometric data

Color T (K)	4000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam angle (°)	110
Beam description	Wide
Efficacy (lm/W)	111
Flux (lm)	5120
SDCM	≤3

Technical data

IP class	IP20
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+35
Calculated LED lifetime, L80 (h)	100 000
Driver lifetime (h)	100 000
Compliance	CE; REACH; ENEC
Guarantee (years)	5

Measurements

Length (mm)	1245
Height/depth (mm)	60
Width (mm)	75
Net weight (kg)	2.5

