

HRC cartridge fuses



Technical data and dimensions (p. 102-103)

Pack	Cat.Nos		Cylindrical type gG			Pack	Cat.Nos		Cylindrical type aM (motor rated)		
			Conform to NF C 63-210/211 - EN 60269-1 and 2 and IEC 60269-1, 2 and 2-1 Veritas approved					Conform to NF C 60-200 - EN 60269-1 IEC 60269-1 Veritas approved			
	Without indicator	With indicator	Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps)		Without indicator	With indicator	Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps)
			10 x 38 HRC						8.5 x 31.5		
10	133 94		0.5			10	120 01		1		
10	133 01		1			10	120 02		2		
10	133 02	134 02	2			10	120 04		4	400	20 000
10	133 04	134 04	4			10	120 06		6		
10	133 06	134 06	6			10	120 08		8		
10	133 08	134 08	8	500	100 000	10	120 10		10		
10	133 10	134 10	10								
10	133 12	134 12	12								
10	133 16	134 16	16								
10	133 20	134 20	20								
10	133 25	134 25	25								
			14 x 51 HRC								
10	143 02		2			10	130 92		0.25		
10	143 04		4			10	130 95		0.50		
10	143 06	145 06	6			10	130 01		1		
10	143 10	145 10	10			10	130 02		2		
10	143 16	145 16	16	500	100 000	10	130 04		4		
10	143 20	145 20	20			10	130 06		6	500	100 000
10	143 25	145 25	25			10	130 08		8		
10	143 32	145 32	32			10	130 10		10		
10	143 40	145 40	40			10	130 12		12		
10	143 50 ⁽¹⁾	145 50 ⁽¹⁾	50			10	130 16		16		
			22 x 58 HRC			10	130 20 ⁽²⁾		20	400	
10	153 04		4			10	130 25 ⁽²⁾		25	400	
10	153 06		6								
10	153 10		10								
10	153 16		16								
10	153 20		20								
10	153 25	155 25	25	500	100 000						
10	153 32	155 32	32								
10	153 40	155 40	40								
10	153 50	155 50	50								
10	153 63	155 63	63								
10	153 80	155 80	80								
10	153 96	155 96	100								
10	153 97 ⁽¹⁾	155 97 ⁽¹⁾	125	400		10	140 45 ⁽¹⁾	141 45 ⁽¹⁾	45	400	
						10	140 50 ⁽¹⁾	141 50 ⁽¹⁾	50	400	



Isolating fuse carriers 8.5 x 31.5 and 10 x 38

see p. 133

Neutral links

10	123 00	8.5 x 31.5
10	133 00	10 x 38
10	143 00	14 x 51
10	153 00	22 x 58



(1) Overrating described by standards
(2) Overrating not described by standards