

22003006

Load break switch SIRCO M 3P 63A 690 VAC Rotary switch



Strong points

- Fully integrated
- A wide range of accessories
- Upgradeability
- Compliance with major certifications and approvals

General characteristics

- Double break by phase.
- Mount on DIN rail, panel or modular panel with 45 mm front cut out.
- IP20 accessories and device.
- Extreme usage categories (AC-22 and AC-23).
- Clear break indication.
- Contact point technology.
- Standard device attaches from the front using the "door mounting kit".

Compliance with standards

- IEC 60947-3
- UL 508, UL98
- GB/T 14048.3

Access to resources (ex: manuals)

SIRCO M are manually operated modifiable and modular multipolar load break switches.

They make and break under load conditions and provide safety isolation for any low voltage circuit, particularly for machine control circuits.

Through the use of accessories, SIRCO M can be transformed into multipolar load break or 3/4 pole changeover switches provide on load changeover switching between two sources or two low voltage power circuits, as well as their safety isolation.

Technical Characteristics

Length of the product unit [mm]	76
Width of the product unit [mm]	52.5
Depth of the product unit [mm]	64
Weight [kg]	0.31
Control operator	Direct : M00 / External : S00, S0, S01
Number of poles	3
Rated voltage	690 VAC - 400 VDC
Rated current [A]	63
Type	Rotary
Frame size	M2

Classification

UNSPSC	39122233
ETIM Class	EC000216
IGCC	5290

Commerce

Description	Manual Load break switch SIRCO M frame M2 with 3 poles, 63A, 690 VAC-400 VDC rotary direct operation with handle type M00 or rotary external operation with handle type S00, S0, S01. Delivered without handle
Effective date	2006-04-13
Offer Life Cycle Code	40
Country of origin	CN
Former product list	25003005-SIRCO VM0 3X63A

Environmental Sustainability

PEP Filename	SOCO-00095-V01.01-EN.pdf
Climate change - Total - Cradle to Grave [kg CO ₂ eq.]	27
Climate change - Total - Cradle to Gate [kg CO ₂ eq.]	2

ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	690
Rated operating voltage [V]	400..690
Rated permanent current Iu [A]	63
Rated permanent current at AC-23, 400 V [A]	63
Rated permanent current at AC-21, 400 V [A]	63
Rated short-time withstand current Icw [kA]	1.5
Rated operation power at AC-23, 400 V [kW]	30

Switching power at 400 V [kW]	30
Conditioned rated short-circuit current I _q [kA]	50
Number of poles	3
ETIM - Mechanical characteristics	
Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	Yes
Suitable for intermediate mounting	Yes
Colour control element	Other
Degree of protection (IP), front side	IP20
ETIM - Technical features	
Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	Yes
Version as reversing switch	No
Number of switches	1
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Other
Interlockable	Yes
Type of electrical connection of main circuit	Screw connection
Logistics	
GTIN/EAN	3596031825431
Customs number	8536508000
Price unit	PC
Weight of the packing unit [kg]	0.3
Length of the packing unit [m]	0.085
Width of the packing unit [m]	0.065
Depth of the packing unit [m]	0.11
Norms	
Conformity to standards	IEC UL