

48290184

RJ45 cable for Digiware bus - Length 2 m



General characteristics

- Available in different lengths.
- 600V insulated, can be in contact with busbars.
- Plug & Play.

Compliance with standards

- IEC 61557-12
- UL

Access to resources (ex: manuals)

The RJ45 connections allow you to connect modules very quickly and to automatically configure connected current sensors:

- communication address,
 - load type,
 - sensor type and ratio,
 - automatic rating and verification of current travel direction.
- Wiring errors are also prevented and installation is simplified.

Technical Characteristics

| | |
|---------------------------------|--------------|
| Length of the product unit [mm] | 2000 |
| Color | Yellow |
| Connector | RJ45 |
| Length | 2 m |
| Type | Digiware bus |

Classification

| | |
|------------|----------|
| UNSPSC | 83101808 |
| ETIM Class | EC001262 |
| IGCC | 6042 |

Commerce

| | |
|-----------------------|------------|
| Effective date | 2013-11-22 |
| Offer Life Cycle Code | 40 |
| Country of origin | TH |

ETIM - Mechanical characteristics

| | |
|-------------------------|--------|
| Length [m] | 2 |
| Colour outer sheath | Yellow |
| Anti-kink sleeve | None |
| Colour anti-kink sleeve | Other |
| Cable construction | 2x4 |
| AWG-size | 24 |
| Cable type | U/UTP |

ETIM - Technical features

| | |
|---|-----------|
| Category | 5 |
| Type of connector connection 1 | RJ45 8(8) |
| Type of connector connection 2 | RJ45 8(8) |
| Locking lever | No |
| Fire retardant version | No |
| Oil resistant according to EN IEC 60811-404 | Yes |
| Pin assignment | 1:1 |
| NVP value [%] | 70 |

Logistics

| | |
|---------------------------------|---------------|
| GTIN/EAN | 3596032776442 |
| Customs number | 8544429090 |
| Price unit | PC |
| Weight of the packing unit [kg] | 0.08 |
| Length of the packing unit [m] | 0.125 |
| Width of the packing unit [m] | 0.03 |
| Depth of the packing unit [m] | 0.06 |

Norms

Conformity to standards

IEC
UL