
**Sevede RE L1250 OP 18W 2200
ActiveAhead-2 830 White**

Article number 36628302256



Product feature

Wireless controls	ActiveAhead
Technology	BT Mesh
Sensor type	PIR
Material of housing	Aluminium (Recycled)
Diffuser/optics	Opal
Color of reflector	White
Light source	Integrated LED
Color of housing	White
RAL	9016

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	18
Standby power (W)	0.5
Qty per B16 MCB	33
Qty per C10 MCB	34
Qty per C16 MCB	56
Power factor	≥0.95

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥80
Light distribution	Direct
Beam angle (°)	110
Beam description	Wide
Efficacy (lm/W)	121
Flux (lm)	2170
SDCM	≤3

Installation data

Mounting	Recessed
Connection	Cable
Length cable (m)	2.5
Material cable	Halogen free

Technical data

IP class	IP20
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+35
Calculated LED lifetime, L80 (h)	100 000
Driver lifetime (h)	100 000
Compliance	CE; REACH; ENEC
Guarantee (years)	5

Measurements

Length (mm)	1245
Height/depth (mm)	60
Width (mm)	75
Net weight (kg)	2.5

