



Sevede PE L1700 MP 50/50 48W 6100 Casambi without sensor 830 White

Article number 26218306159

Sevede is our linear premium solution for office lighting. Available in white or black and two lengths as standard. Unique is that you can create a homogeneous light line in desired length. Available in four types of optics: opal, micro prismatic, lens and lens asymmetric optics. Housing is made of at least 75% recycled aluminium - Hydro Circal - for a lower carbon footprint. Available with ActiveAhead or Casambi. Wire suspension delivered with luminaire is adjustable up to 1000mm.

Product feature

User interface	Casambi
Technology	BT Mesh
Driver type	DALI-2
Material of housing	Recycled aluminium
Diffuser/optics	Microprismatic (MP)
Color of reflector	White
Light source	Integrated LED
Color of housing	White
RAL	9016

Installation data

Mounting	Pendent
Cable entries	1
Connection	Cable
Length cable (m)	2.5
Material cable	Plastic non-PVC

Electrical data

Frequency (Hz)	0/50-60
Voltage (V)	220-240
Isolation	Class 1
Power (W)	48
Standby power (W)	0.5
Qty per B16 MCB	18
Qty per C10 MCB	19
Qty per C16 MCB	31
Power factor	≥0.95

Photometric data

Color T (K)	3000
Color Rendering Index (CRI)	≥80
Light distribution	Direct; Indirect
Distribution (Up/down)	50/50
Beam angle (°)	90
Beam description	Medium wide
Unified Glare Rating (UGR)	≤19
Efficacy (lm/W)	124
Flux (lm)	5970
SDCM	≤3

Technical data

IP class	IP20
Ambient temp, min (°C)	+10
Ambient temp, max (°C)	+35
Calculated LED lifetime, L80 (h)	100 000
Driver lifetime (h)	100 000
Compliance	CE; REACH; ENEC

Measurements

Length (mm)	1723
Height/depth (mm)	75
Width (mm)	55
Net weight (kg)	4.2

