

## **Collina CE D400 DALI**

Article number 465338



#### Product feature

|                                    |                    |
|------------------------------------|--------------------|
| <b>Driver type</b>                 | DALI-2             |
| <b>Material of housing</b>         | Polycarbonate      |
| <b>Material of diffuser/optics</b> | Polycarbonate (PC) |
| <b>Diffuser/optics</b>             | Opal               |
| <b>Light source</b>                | Integrated LED     |
| <b>Color of housing</b>            | White              |
| <b>RAL</b>                         | 9016               |
| <b>Gtin</b>                        | 7333160038990      |

#### Installation data

|                               |                      |
|-------------------------------|----------------------|
| <b>Mounting</b>               | Surface              |
| <b>Installation (surface)</b> | Wall                 |
| <b>Cable entries</b>          | 4                    |
| <b>Connection</b>             | Terminal block 5x2.5 |
| <b>Looping</b>                | Yes                  |

#### Electrical data

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| <b>Frequency (Hz)</b>     | 0/50-60                                                    |
| <b>Voltage (V)</b>        | 220-240                                                    |
| <b>Isolation</b>          | Class 2                                                    |
| <b>Power (W)</b>          | 25                                                         |
| <b>Available with</b>     | Emergency versions available on request; Integrated sensor |
| <b>Type Of Connection</b> | Push-in terminal                                           |
| <b>Power factor</b>       | ≥0.90                                                      |

#### Photometric data

|                                    |                  |
|------------------------------------|------------------|
| <b>Color T (K)</b>                 | 3000; 4000; 5700 |
| <b>Color Rendering Index (CRI)</b> | ≥80              |
| <b>Light distribution</b>          | Direct           |
| <b>Beam angle (°)</b>              | 120              |
| <b>Beam description</b>            | Wide             |
| <b>Unified Glare Rating (UGR)</b>  | ≤25              |
| <b>Efficacy (lm/W)</b>             | 116              |
| <b>Flux (lm)</b>                   | 2900             |
| <b>SDCM</b>                        | ≤3               |

#### Technical data

|                                         |                 |
|-----------------------------------------|-----------------|
| <b>IP class</b>                         | IP54            |
| <b>IK class</b>                         | IK08            |
| <b>Ambient temp, min (°C)</b>           | -20             |
| <b>Ambient temp, max (°C)</b>           | +40             |
| <b>Calculated LED lifetime, L80 (h)</b> | 100 000         |
| <b>Compliance</b>                       | CE; REACH; ENEC |
| <b>Guarantee (years)</b>                | 5               |

#### Measurements

|                          |     |
|--------------------------|-----|
| <b>Height/depth (mm)</b> | 59  |
| <b>Diameter (mm)</b>     | 400 |
| <b>Net weight (kg)</b>   | 1.6 |

