



lighting management - stand alone

detectors, power packs



488 03



488 20



488 07



488 06



Technical characteristics (p. 913)

Pack	Cat.Nos	Traffic detection - Infrared technology
1	488 03 	Ceiling mounting detector Set via a thumbwheel 360° - detection Ø: 7 m IP 20
1	Grey 697 40 White 697 80 	Wall mounting detector 360° - detection range: 12 m IP 55
1	488 11 	270° - detection range: 15 m IP 42
Passage detection - Infrared technology		
1	488 01 	Set via a thumbwheel. With manual ON, can be switched on manually/switched off automatically Possible override with remote control Cat.No 882 31 and configuration tools Cat.Nos 882 30 or 882 35 Ceiling mounting detector 360° - for areas up to 47 m²
1	488 02 	Ceiling mounting detector with fast connection connector 360° - for areas up to 47 m²
Detectors with power packs		
1	488 50 	Power packs For large areas or where several circuits are necessary Set via a thumbwheel. With manual ON, can be switched on manually/switched off automatically Up to 10 detectors can be connected to power packs 2 outputs: 1 x 16 A + dry contact 1 volt-free output for connecting a VMC or a second lighting load
1	488 20 	Flush-mounting detectors for power packs Wall-mounting detector - IR 360° - for 47 m² areas
1	488 21 	Ceiling mounting - Ultrasonic 360° - for 190 m² areas
1	488 22 	Wall-mounting detector - dual-technology 360° - for 93 m² areas
1	488 23 	Surface-mounting detectors for power packs Wall-mounting detector - dual-technology 270° - 15 m range
1	488 24 	Wall-mounting detector - IR 270° - 15 m range
1	488 30 	Wall-mounting detector - IR 270° in main areas detection (in front, range 16 m) 360° for areas below the product (better detection when installed above a door opening) IP 55

Pack	Cat.Nos	Digital passage detector, preset
1	488 07 	IR/Ultrasonic or dual-technology Factory settings: - light level: 500 lux - time delay: 20 minutes - walkthrough function activated - retrigger mode active - adjustment by IR commissioning tool Can be switched on manually/switched off automatically remote control Cat.No 882 31 and configuration tools Cat.No 882 30 or Cat.No 882 35
1	488 08 	For small areas, technical places Ceiling mounting detector - IR 360° - for 47 m² areas IP 20
1	488 05 	Ceiling mounting detector equipped with fast connection connector 360° - for 47 m² areas
1	488 06 	For large areas, stairwells... Ceiling mounting detector - Ultrasonic For 190 m² areas IP 20
1	488 10 	For all types of areas Ceiling mounting detector - dual-technology For 93 m² areas IP 20 Wall-mounting detector - IR 270° in main areas detection (in front, range 16 m) 360° for areas below the product (better detection when installed above a door opening) IP 55