

48250604

Power quality meter DIRIS A-200 RS485+Ethernet MODBUS sensor



Strong points

- The ultimate all-purpose power quality meter
- Plug & play
- Fully customizable
- Advanced features*
- Best-in-class accuracy
- Easy data management

Compliance with standards

- IEC 61557-12
- IEC 62053-21 -24
- UL 61010-1 File E257746
- ISO 14025
- EN50160

Link to the reference



<https://emea.socomec.com/en/reference/48250604>

The DIRIS A-100 / A-200 are panel-mounted power quality meters that can communicate either via MODBUS RTU over RS485, MODBUS TCP over Ethernet or BACnet IP. The device's four RJ12 independent current inputs enable the management of multiple circuits of several different types: for example, 4 single-phase loads or 1 three-phase load + 1 single-phase load. A core-balance toroid can be fitted onto the A-200 for additional residual current monitoring. Most types of sensors are compatible: solid-core, split-core or flexible Rogowski coils through quick-connect RJ12 sensors.

Classification

UNSPSC	83101808
ETIM Class	EC002301
IGCC	6042

Commerce

Description	Power quality meter DIRIS A-200, WEBVIEW web interface RJ12 current sensor, 115-600 VAC power supply with Modbus communication protocols and RS485, dual ethernet communication ports, Solid-core, Split-core or Rogowski coils are compatible
Effective date	2023-06-01
Offer Life Cycle Code	40
Country of origin	US

Environmental Sustainability

Climate change - Total - Cradle to Grave [kg CO ₂ eq.]	377
Climate change - Total - Cradle to Gate [kg CO ₂ eq.]	41
SVHC > 0.1 mass percentage?	No
RoHS applicable?	Yes

ETIM - Electrical characteristics

Accuracy class active energy according to IEC 62053-22	0.1S
Accuracy class reactive energy according to IEC 62053-23	Other
Pulse output	Electrical
Sampling frequency [Hz]	9600
Number of voltage measurement inputs	4
Number of current measurement inputs	4
Voltage type (supply voltage)	AC
Supply voltage AC 50 Hz [V]	115..600
Supply voltage AC 60 Hz [V]	115..600
Measuring range for frequency [Hz]	50..60
Max. current (Imax) [A]	10000
Display resolution (horizontal) [px]	350
Display resolution (vertical) [px]	160
Number of digital inputs	3
Number of digital outputs	1
Number of Ethernet-connections	2

Suitable for RJ plug	Yes
Supporting protocol for IEC 61850 Ethernet	No
Supporting protocol for OPC UA PubSub	No
Supporting protocol for PROFIBUS	No
Supporting protocol for Modbus	Yes
Supporting protocol for PROFINET IO	No
Supporting protocol for other bus systems	Yes
With firmware signature	Yes
With logging of security events (security event log)	Yes
Web server with HTTPS transfer protocol	Yes

ETIM - Mechanical characteristics

Mounting method	Front mounting
Width [mm]	98.5
Height [mm]	98.5
Depth [mm]	108
Degree of protection (IP), front side	Other

ETIM - Technical features

Display	Graphic
Remote display	No
With communication interface KNX	No
With communication interface M-Bus	No
With communication interface RS-485	Yes

Logistics

GTIN/EAN	3596033205484
Customs number	9030320000
Price unit	PC
Weight of the packing unit [kg]	0,44
Length of the packing unit [m]	0,135
Width of the packing unit [m]	0,12
Depth of the packing unit [m]	0,11

Technical Characteristics

Height [mm]	98.5
Width [mm]	98.5
Depth [mm]	108
Weight [kg]	0.349
Application	Analysis
Communication ports	RS485 + Dual Ethernet
Communication protocols	Modbus RTU; Modbus TCP; BACnet IP
Model	A-200
Type	RJ12